

Product datasheet

Specifications



Occupancy Sensor, C-Bus Control and Management System, Passive Infrared

5751L-WE

Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Occupancy sensor
Device application	Lighting
Product specific application	Staircase monitoring
Sensor type	PIR
Colour	White electric

Complementary

Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable
Number of channels	1
Detection face	Lateral: 6 m Frontal: 8.5 m
Movement detection area	6 m
Horizontal detection angle	0...120 °
Vertical detection angle	90 °
Time delay range	0...1 s (switch-on)
Duty cycle	1080 min
Material	Plastic
Device mounting	Surface
Mounting height	2.4 m
Colour code	WE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.8 cm
Package 1 Width	12.0 cm
Package 1 Length	11.7 cm
Package 1 Weight	180.0 g
Unit Type of Package 2	CAR

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 2	20
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.9 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	320
Package 3 Height	120.0 cm
Package 3 Width	60.0 cm
Package 3 Length	80.0 cm
Package 3 Weight	88.4 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	6 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	27
End of life manual availability	End of Life Information
Take-back	No