

Product datasheet

Specifications



PIR Occupancy Sensor, C-Bus Control and Management System, Flush Mount, 360 Degree

5753L

Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Occupancy sensor
Device application	Lighting
Product specific application	Staircase monitoring
Sensor type	PIR
Colour	White

Complementary

Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable
Number of channels	1
Time delay range	0...1 s (switch-on)
Detection face	Lateral: 7.5 m Frontal: 7.5 m
Movement detection area	15 m
Horizontal detection angle	0...360 °
Duty cycle	1080 min
Material	Plastic
Device mounting	Flush
Mounting height	2.4 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.529 cm
Package 1 Width	12.706 cm
Package 1 Length	16.538 cm
Package 1 Weight	200 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	30 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	43.2 cm
Package 2 Length	22 cm
Package 2 Weight	2420 g
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	47720 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	7 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	27
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins