Product datasheet

Specifications



Relay, C-Bus, DIN Rail Mounted, Shutter, 240V AC, 1 Channel, 2A, Without C-Bus Power Supply

L5501RBCP

Main

Range of product	C-Bus
Product brand	Clipsal
Range	C-Bus
Product or component type	Relay
Device application	Control

Complementary

Local signalling	LED
[Us] rated supply voltage	15...36 V DC
Width	36 mm
Height	93 mm
Depth	63 mm

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	10.6 cm
Package 1 Length	15.2 cm
Package 1 Weight	144.0 g

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	238
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Halogen free product
PVC free	No
Silicone-free	No

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins