Product datasheet

Specifications



Twin gang 13A 250V Ulti switched BS socket module, amber LED

UST25-A00

Discontinued on: 30 Jun 2023

Discontinued

Main

Range	Ulti
Device application	Power supply
Product or component type	Socket-outlet
Number of gangs	2 gangs
Bulb type	LED amber
Rated current	13 A at 250 V AC 50 Hz

Complementary

[Us] rated supply voltage	250 V AC
Device mounting	Surface Flush
fixing mode	By screws
Wiring device mounting	Flush Surface

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations